

Cathodic Protection Products

The LifeAnode™ system is an engineered galvanic “discrete” or “point” anode designed for patch repairs for damaged concrete due to chloride induced corrosion.

The sacrificial anode system consists of anode grade zinc encased in a specially formulated conductive mortar, designed to maintain anode activity without excessive self-corrosion.

Adding LifeAnode systems to a concrete patch repair job adds 10-15% to the cost; however, These anodes prevent halo- or ring-effect corrosion, thus preventing follow up repairs to the area in 3 - 5 years. In other words, LifeAnode systems can prevent long term repairs that could add up to 100% of the original repair cost.





Cathodic Protection Products

Contact our sales team for more information about our company and products.

Toll-Free:
(800) 251-7506

Phone:
(228) 257-1356

Fax:
(423) 639-3125

Email:
Nancy.Le@artazn.com

Website:
artazn.com

Address:
ARTAZN
P.O. Box 1890
Greeneville, TN 37744-1890

The information of Artazn LLC (the "Company") contained in this Product Data Sheet (this "Sheet") is furnished to recipient (a) without charge or obligation and (b) as of the date of publication hereof, and remains subject to revision at any time. Recipient accepts the information at its sole risk and the Company makes no representation or warranty with respect to the information herein, including the accuracy thereof, and assumes no liability in connection with any reliance on, or application or use of, the information and/or products herein. This Sheet in no way modifies, amends, or expands any specifications or warranty of the Company.

Product Features:

- ◆ Anode (Zn) Mass: 65 grams
- ◆ External Anode Dimensions: 4.5" x 2.75" x 0.75"
- ◆ External Surface Area: 35 in²
- ◆ Zinc Anode Surface Area: 21 in²
- ◆ Specially configured galvanized tie wires for ease of installation and extended throwing power
- ◆ Anode Composition: conforms to ASTM B418, Type II
- ◆ Anode Spacing: industry norm

Performance Features:

- ◆ Anode Potential: more negative than -950 mV, CSE, when pre-moistened
- ◆ Capacity: >800 A-hr/kg
- ◆ Auto-Corrosion: "Nil" (<0.1 mm / year)
- ◆ Maintains anode activity and adjust output with changes in environmental conditions

Packaging:

- ◆ Quantity per box: 30
- ◆ Box Dimensions: 15.75" long x 9.625" wide x 9.625" high (0.40 m x 0.24 m wide x 0.24 m high)
- ◆ Box Weight: 16.3 lbs (7.4 kg)
- ◆ Units per Skid: 900

Storage:

- ◆ Avoid extreme temperatures and moisture; nominal shelf life 5 years

Other Cathodic Protection Products:

LifeJacket®

LifePanel®

LifeDowel™